

Prep™ Supreme

1/2

Version 06 / Version date 2016.04.25

Product No: 7498-420 (AAK-SE)

Description

Prep™ Supreme is a refined vegetable oil. Prep™ Supreme is pourable at room temperature and has a good stability against oxidation.

Application

Prep™ Supreme is used for snack food, cereals and for deep frying of pre-fried foods such as potato chips, chicken, fish, meat, vegetables etc. As a result of its low melting point, it is also very easy to use.

Specifications

Free fatty acid as palmitic acid (%)	Max 0,1	IUPAC 2.201(m)
Peroxide value (meq/kg)	Max 0,5	AOCS Cd 8b-90(m)
Iodine value Wjjs	Min 65	IUPAC 2.205
Flavour	Neutral	Sensoric

Typical values

Density 30°C (g/cm3)	0,91	Electronic density meter
Solid fat content		IUPAC 2.150(a)
0°C (%)	10	
10°C (%)	0	
Oil stability index 120°C (h)	11	AOCS Cd 12b-92(m)
Saturated fatty acids (%)	37	IUPAC 2.304
Monounsaturated fatty acids (%)	49	IUPAC 2.304
Polyunsaturated fatty acids (%)	14	IUPAC 2.304
Trans fatty acids (%)	Max 1	IUPAC 2.304

Additives

Anti-foaming agent E900

Ingredients (in varying proportions)

Vegetable oil (palm), anti-foaming agent E900.

Above product is produced according to relevant national legislation. Specified values are guaranteed ex-works AAK factories. As the specific application is beyond our control, users should conduct their own tests to assure the suitability of the product for a specific application.

www.aak.com

Prep™ Supreme

Version 06 / Version date 2016.04.25

Product No: 7498-420 (AAK-SE)

Nutritional values (typical values per 100g)

Energy (kJ/kcal)	3700 / 900
Fat (g)	100
Saturated fatty acids	37
Monounsaturated fatty acids	46
Polyunsaturated fatty acids	12
Protein (g)	0
Carbohydrates (g)	0
of which sugars	0
Salt (g)	0

Packaging

Bucket 10L

Pallet

4 layer/pallet

12 buckets/layer

48 buckets/pallet net weight 437,28 kg

Net weight/bucket 9,11 kg

Storage

Dry and cool / room temperature.

Heat to room temperature and stir before use.

Recommended shelf life

12 months from production date in unopened package.

Above product is produced according to relevant national legislation. Specified values are guaranteed ex-works AAK factories. As the specific application is beyond our control, users should conduct their own tests to assure the suitability of the product for a specific application.

www.aak.com